

The Music & Passion of Barry Manilow

2023 Technical Rider

Thank you for taking the time to read this rider. The purpose of this rider is to ensure the best possible concert experience for your audience.

DAYBREAK is a full, live band that requires certain technical provisions to ensure a trouble-free performance. Please read this rider carefully and if any of our requirements cannot be met, please contact the appropriate agent or representative listed below immediately.

Tour Personnel

Production Manager/FOH - Show Advance

Todd Fink 262-844-9070 <u>toddlymixes@sbcglobal.net</u>

Tour Manager

Bruce Peterson 262-366-8843 bruce@copaentertainers.com



2023 Technical Rider

1. HOSPITALITY

- Coffee/tea with half and half or milk (no Coffee Mate please)
- Two (2) Cases of Bottled Water 1 Room Temp, 1 Cold
- 8 clean hand towels
- Dinner for (10) people from local restaurant. Band will order off menu.
 A \$20.00 per person meal buyout is also acceptable
- Private Dressing Rooms

Please provide two (2) heated / air-conditioned locking dressing rooms and spare keys to be given to the tour manager upon arrival. Dressing area should contain: tables and chairs, trash receptacle, clothes rack and hangers, full-length mirror, private restrooms.

2. SOUND REQUIREMENTS

Purchaser to provide a first class sound system as follows:

• FOH Speaker System

A professional quality, state of the art, stereo sound system capable of even coverage over the entire audience area, with the ability to produce a clear, undistorted 110db at FOH Mix Position. Preferred speaker manufacturers are d&b, JBL, Meyer, L'Acoustics. All systems MUST include proper processing and time alignment in advance of Daybreak arrival. Daybreak FOH engineer has complete access to all system processing, if necessary.

The Daybreak show requires front fill speakers for any venue in which the main left and right house PA speakers are more than 20' apart. Front fill speakers are to be placed across the entire down stage lip (no further than 6' apart) capable of reproducing a full band mix (hi-passed@120Hz), fed from an aux send, post fader. The performance also requires Aux fed subs, post fader and graphic equalizers for each of these 2 mixes.



FOH Mix position should be no less than 50' and no more than 100' from the downstage edge, centered with the speaker system.

• FOH Console

A professional digital mixing board, in perfect working condition, with a minimum of 32 dedicated inputs and (4) effects processors is required. Preferred mixing consoles are Digico SD-10, SD-8, SD-9, Soundcraft SI Impact, any professional digital console should be fine, no Behringer or Mackie. *Any substitutions MUST be discussed and agreed to before the show. No side stage or iPad mixing.*

FOH Talkback switchable handheld mic sent to stage monitor console at LINE level.

Male 1/8" TRS to 2 male XLRs for FOH IPOD audio playback prior to sound check for system verification.

Monitors

The band carries its own racked mixer , with stage boxes, mics, stands, DI's cables & analog snake split for monitoring their own IEM's (8 mixes.) This will generally live off stage left, with a little flexibility depending on how the sub snakes reach in each stage situation. For certain fly dates, they will not be carrying the racked mixer. In this case, a monitor engineer with a separate console is needed.

Microphones / DI's / Mic stands/ Cabling

The band carries all mics, DI's, stands, sub snakes with XLR tails to interface with house snake. Band does not carry any power drops for stage. See plot for placement.

• On Stage Announcements

Any on stage announcements must be conducted from a separate in-house microphone and stand. Once the stage is set, the microphones for DAYBREAK should not be touched.

• Lighting

DAYBREAK travels with a lighting guide for in-house LD's that provides general lighting instructions, by song and set list, for the show.

DAYBREAK requires a downstage front lighting wash in warm white and a minimum of 4 focusable downstage Lekos or similar lighting fixtures for specials. DAYBREAK also requires, at minimum, a four-color wash, upstage for backlighting.



• Stage Requirements

Stage shall be constructed of professional grade manufactured steel, aluminum, concrete or wood that meets a minimum load bearing weight of 6500lbs. Ramp shall be sturdy and non-slip.

Stage Dimensions

Stage shall be a minimum of 24' wide x 16' deep x 2' high, with an unobstructed off stage left area of at least 8' x 8' for Artist Technical Personnel.

- If this is an outdoor engagement, the stage and all work areas pertaining to the stage including Artist's personal equipment and Artist's Technical Personnel must be completely covered and protected from the elements by either an existing structural roof, canopy, or a professional level mobile stage (such as an SL-100 or SL-320.).
- EZ-ups and/or tarps are not acceptable stage covering for sufficient outdoor protection.
- Artist retains the right to refuse the performance if stage or any work areas
 pertaining to the stage are deemed unsafe due to standing water, improper
 electrical grounding or any other potential hazard to personnel OR equipment.

• Stage Risers

One (1) 8'x 8' x 2' CARPETED drum riser is required. Drum riser shall be manufactured from sturdy and professional grade materials such as aluminum or steel consisting of 4 x 8 sections that lock together. Two (2) 4' x 8' x 1' risers are also required, 1 USL for bass player and one USR for BGV.

Backline Power

A minimum of (2) dedicated, 20-amp 110v circuits (not to be combined with audio or lighting power) are required for Artist's backline and personal gear as per stage plot.

(1) Audio technician familiar with the house / monitor sound system and house power.

4



2023 Technical Rider

(1) Lighting operator

Any questions or substitutions regarding this rider MUST be discussed with and agreed upon BEFORE any changes are made

5. BACKLINE REQUIREMENTS - ONLY IF DAYBREAK IS CONTRACTED WITHOUT INSTRUMENTS

A Backline Technician from the backline company should be onsite for the entire setup, show, & strike.

Please include all IEC, speaker cables, footswitches, clamps, cables, etc. should be included with the backline listed below for proper operation.

Guitar - Phil

Fender Deluxe Reverb, Twin, or Roland JC120.

- One (1) Electric Guitar as a backup: Fender Stratocaster or Telecaster.

Two (2) Single Guitar Stands

Bass - Manny

Aguilar AG700 bass head or equivalent Markbass 4 x 10 bass cabinet or equivalent Music stand w/ light (and clips if outdoors) Adjustable stool

Keyboard - Jody

88 key weighted MIDI controller or stage piano (USB capable for laptop connect)
Roland Fantom 07 Synthesizer
2 tier Keyboard stand
I-Pad holder w/ adjustable height or music stand
Adjustable stool
Laptop stand w/ adjustable height

Keyboard - Joey B

88 key weighted MIDI controller or stage piano (USB capable for laptop connect)

5



Keyboard stand Music stand w/ light (and clips if outdoors) Adjustable stool Laptop stand

Piano-Joe

Digital Piano weighted 88 key - Korg Grandstage or Roland RD2000 (or equivalent. Please submit for approval)
Grand Piano Shell that fits above keyboard
Adjustable drum throne

Drums-Hosney

DW collectors, design or Gretsch preferred.

22" Kick

DW 9000 Single kick pedal

14 x 6 ½ " Snare

12" rack tom

14" floor tom

16" floor tom

Cymbals should be Zildjian K

22" ride cymbal

15" high hats


3 crash cymbals 18", 19", 20"

Round/flat top throne

HH, snare, (5) Cymbal stands

Drum rug

** NO SUBSTITUTES ARE ACCEPTABLE WITHOUT PRIOR APPROVAL **



DAYBREAK Provides Inputs connect X-32 Rack 9 \$ 24 Non Rack men To All Mics, TOIL VIA OUT Stands Split >Id And cables

sketch NOTES

- 1 KICK 2 Snare 3 HI HAT
- 4 RACK 1
- FLOOR - RACK 2
- 7 OH SR
- 8 0HSL
- BASS
- 10 GUITAR
- 12 SR KEY R 11 - SR KEY L
- 13 FLUGELHORN
- 14 open
- 15 SL KEY

9

open

- PIANO R - PIANO - L
- 19 STAR VOC W/L
- 20 STAR VOC wired spare 21 BGV 1 22 BGV 2
- 31 band TB mon only 32 FOH TB
- www.napkinsketchapp.com Napkin Sketch



DAYBREAK